



Type F-YRD

Yeast-Raised Donut Depositor

Belshaw now offers a version of its Type F depositor for yeast-raised donuts. With the Type F-YRD, rolling and cutting dough are unnecessary. The depositor fills a fryer screen in under 60 seconds, and produces great tasting, well-rounded ring donuts.

- Raised donut mix, including Pressure-cut donut mix, can be used.
- Donuts are deposited directly onto a fryer screen.
- Donuts are proofed like any other raised donut
- Donuts are fried normally.
- Type F-YRD employs a special plunger to deposit dough, usable for yeast-raised ring donuts only
- The adjustment dial at the side of the Type F-YRD allows a range of batter weights for each deposit.
- The Type F-YRD utilizes a motor and trigger handle to deposit at a rate of 57 per minute when the trigger is held down.
- The Type F-YRD is compatible with all open kettle fryers. It can also be used in conjunction with Donut Robot® systems
- Belshaw depositors, the industry standard for many years, are legendary for their precision and smoothness of operation - even after many years of use. Each depositor is engineered of durable gears, cams and trip arms to produce near-identical volume and shape with every deposit.



VIDEO



PDF



WWW

Serving bakeries for **99** years

www.belshaw.com

Standard features

- Aluminum alloy frame
- Hardened steel cams
- Bronze trip arms and bushings
- Batter weight adjustment dial
- Aluminum hopper (Capacity 15 lbs/6.8 kg)
- Heavy duty motor
- Fan cooled
- Includes thermally protected circuit breaker
- Hand trigger control up to 57 cycles/minute
- Plunger-Cylinder-Metering Tube (one size only)

Accessories

- TPE F-YRD package, including Depositor, Table on wheels, with mount for Type F-YRD (#FVMRF-1000)
- Type B/F Column Mount (#0405)
- Wall Mount (#0406)
- Bracket Arm Height Adjuster (#0400)

Plungers and cylinders

- The plunger used by the Type F-YRD is suitable for ring donuts only, up to approximately 4 inches diameter (dependent on mix and proofing).

Electrical options

- 120 Volts, 60 Hertz, 1-phase, 950W, 7.9 Amps
- 240 Volts, 50/60 Hertz, 1-phase, 960W, 4 Amp

Item numbers

Item Nbr.	Description
F0050000	Type F-YRD depositor with hopper, plunger, cylinder and metering tube, 115V
F0050001	Type F-YRD depositor with hopper, plunger, cylinder and metering tube, 230V, 50/60hz, 1ph
F-YRD Package 115 V	F0050000 with depositing table (shown at right)
F-YRD Package 230 V	F0050001 with depositing table (shown at right)
FVMRF-1000	Depositng table for Type F-YRD including mounting system
0405	Column mount bracket kit for Type B or Type F
0406	Wall mount bracket kit, Type B or Type F
0400	Bracket Arm Height Adjuster. Enables quick accurate adjustment to height of depositor. (For column mount only)
0290	Hopper for Type B or Type F
VMRF-1016	Plunger for Type F-YRD
VMRF-1010	Cylinder for Type F-YRD
VMRF-1011	Metering tube for F-YRD

Net dimensions

- Type FYRD package (depositor mounted on table as shown below):
48" Wide x 43" Deep x 55 ¾" High (122 cm W x 109 cm D x 141.6 cm H)

Shipping weights and dimensions

- #F0050000 Type F-YRD Yeast Raised Depositor, on pallet: 48"x40"x30", 133 lbs (122 x 76 x 76 cm, 60.5 kg) Freight class 85
- F-YRD Package, includes depositor and table, below: 53"x58"x63", 488 lbs (135 x 147 x 160 cm, 160 kg) Freight class 85

Certifications



- North America models certified by NSF (Standard 169)
- CE models available for European Union and other countries



Type F-YRD Package with depositing table #FVMRF-1000



Type F-YRD Plunger-cylinder-metering tube

Serving bakeries for **99** years

www.belshaw.com